



BONDING PRIMER

dispersive agent for priming substrates
beneath structural plasters and paints



HIGH
BONDING



EASY IN USE



APPLY WITH
BRUSH/ROLLER

USE

The product is used for priming substrates beneath plasters and wall decorations. Owing to special selection of components it improves bonding and unifies substrate absorptiveness.

Place of use: walls and ceilings indoors.

Substrate type: plasters, concrete, plasterboards, wood-like and any sound, previously cleaned and prepared substrates.

PROPERTIES

Contains aggregate (forms rough surface); improves bonding (strongly adheres to substrates and plasters applied); reduces absorptiveness and strengthens substrates; facilitates plasters application and texturing; unifies the substrate colour.

TECHNICAL DATA

Density	approx. 1.2 g/cm ³
Temperature of use	from +5 °C to +30 °C
Number of coats	1
Time of drying	4-6 h
Tack-free surface	2 h

*Time recommended for application in temperature approx. 23°C and humidity 55%; in lower temperature and higher humidity time can extend.

The product has been given the Hygienic Attest. It meets the requirements of standard PN-C-81753:2002.

APPLICATION

Substrate preparation

The substrate should be appropriately sound, stabilized, free of layers which would impair product bonding, in particular of dust, dirt, lime, oils, grease, residues of paints and other.

Product preparation

The product is delivered ready to use. Mix well before use in order to unify its consistency.

Application

Apply with a single uniform coat. Use a roller or a paintbrush.

CONSUMPTION

Average consumption: approx. 0.1 kg/m² per coat (1 kg of product for approx. 7 m²). The actual consumption depends on substrate texture and absorptiveness, quality of substrate preparation, expected decorative effect, technique of application, user's experience, number of coats.

IMPORTANT ADDITIONAL INFORMATION

- Keep out of reach of children. Avoid contact with skin and eyes. After direct contact with eyes – wash with plenty of water and contact a doctor, Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a doctor, show package or label. Follow the instructions of the Safety Data Sheet.
- Keep in tightly sealed original and labeled containers. Keep in dry and cool places, protect against overheating (> 30 °C) and freezing. Shelf life in conditions as specified is 24 months from the production date shown on the packaging.

PACKAGING

Plastic containers: 1 kg, 3 kg

The above information constitutes basic guidelines for the application of the product and does not release the user from the obligation of carrying out works according to engineering principles and OHS regulations.

At the time of publication of this product data sheet all previous ones become void. Date of update: 2016-10-17



www.fox-dekurator.pl