

USE

Application of thin-coat decorations – forms exclusive decorative coating coming back to antique techniques of decorating. Its surface is characterised by great gloss with optic spatial depth.

Place of use: walls and ceilings indoors.

Types of substrate: plaster, concrete, stone, plasterboards, wood-like boards and any other sound, clean and appropriately prepared substrate.

PROPERTIES

Durable top finish; resistant to wet washing; gives effect of grinded marble

APPLICATION

Substrate preparation

The substrate should be: sufficiently sound, stable, free of layers which would impair product bonding, in particular dust, dirt, lime, oils, grease, residues of paints and other.

Primed - with FOX DEKORATOR BONDING PRIMER.

Product preparation

The product is delivered ready to use. Mix well before use in order to unify its consistency.

Colouring

With FOX DEKORATOR system of tube pigments or in NCS colour scheme.

Plastering

Plan the order and way of application before work, check the final effect on a small sample first!

The plaster is applied in three coats with a stainless steel trowel. During application of the first coat form the "drawing" which will show up as the effect at the final coat polishing. The subsequent STUCCO coats should be applied when the previous ones dry completely. Carry out application upon the whole surface similarly.

After application of the third coat, when the coat keeps drying, the STUCCO should be polished with a trowel sharp edge led upon the decoration surface.

Apply stencils used for application of decorative effects before application of the first or the second plaster coat. The effects show up as decorative discolouration during polishing of the final coat.

Protection

FOX DEKORATOR DECORATIVE WAX is applied with a trowel upon the surface 0.5 up to 0.7 $\rm m^2$ large and uniformly distributed with a thin coat; polish the surface then after.

CLASSIC STUCCO

semi-transparent structural interior plaster







FOR INDOOR USE

APPLY WITH SPATULA/TROWEL

CONSUMPTION

Average consumption: $0.5-0.6~{\rm kg/m^2}$ per coat (1 kg of product for approx. 2 m² of decoration). The actual consumption depends on substrate texture and absorptiveness, quality of substrate preparation, expected decorative effect, technique of application, user's experience, coat thickness.

TECHNICAL DATA

Density: 1.6 kg/dm³

Temperature of use: from $+5^{\circ}$ C up to $+30^{\circ}$ C, the time of drying can

extend in low temperature and/or high humidity

Number of coats: 1-3

Time of drying: tack-free surface after approx. 2 h Application of subsequent coat: after 6 h Dilution: water – dilute in 5-10% of water if needed

Technical requirements: Hygienic Certificate issued by Polish Insti-

tute of Hygiene Shelf life: 24 months

TECHNICAL REQUIREMENTS

FOX DEKORATOR CLASSIC STUCCO meets the requirements of PN-EN 15824:2010 standard. Declaration of Performance no. 302/CPR.

C€	PN-EN 15824:2010 (EN 15824:2009)
Decorative plaster manufactured in dry powder form, for indoor use on walls, posts and partition walls.	
Reaction to fire – class	С
Bonding	≥ 0.3 MPa
Thermal conductivity coefficient (\(\lambda_{10, dry}\))	1.28 W/mK Average tabular value P=90% (EN 1745:2002 tab. A.12)
Release/content of hazardous substances	See: Safety Data Sheet



IMPORTANT ADDITIONAL INFORMATION

- May cause respiratory irritation. Causes skin irritation. Causes serious eye damage. Keep out of reach of children. Avoid breathing dust. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or a rash occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do continue rinsing.
- Tools must be cleaned with clean water directly after use.
- Transport and store in tightly sealed packages, in dry conditions. Protect against overheating and freezing.

PACKAGING

Plastic containers 1 kg, 4 kg, 8 kg

The above information constitutes basic guidelines for the application of the product and does not release the user from the obligation of carrying out works according to engineering principles and OHS regulations.

At the time of publication of this product data sheet all previous ones become void. Date of update: 2016-10-18



